



Model 3220 Specifications

UPRIGHT VACUUM

| Feature | | English / Metric |
|--|---|------------------|
| Brush Drive System | | |
| Brush belt description | Dual, round drive belts | |
| Brush type | Single row, chevron pattern | |
| Brush size | 2.25-inch/ 57 mm-diameter 12-inch/ 305 mm-length | |
| Brush power | 0.1 hp/ 0.07 kW | |
| Brush motor RPM | 6000 rpm | |
| Brush RPM | 3000 rpm | |
| Brush height | Adjustable to 6 positions w/ manual dial | |
| Vacuum System | | |
| Airflow @ 2.1-inch/ 53 mm Orifice | 125 cfm/ 3.53 m ³ /h | |
| Waterlift at sealed Orifice | 80-inch/ 2032 mm | |
| Vacuum motor type | Through flow, single stage; thermal protected | |
| Vacuum motor power | 1.0 hp/ 0.7 kW | |
| Chassis & Body Construction | | |
| Chassis & Body Construction | Rotationally-molded polyethylene | |
| Electrical | | |
| Indicator light | Multi-signal light system for improved safety | |
| Electrical system | Printed circuit board protected | |
| Machine Dimensions | | |
| Length | 14.5-inch/ 370 mm | |
| Machine Width | 14-inch/ 355 mm | |
| Height | 47-inch/ 1195 mm | |
| Weight | 21 lb/ 9.5 kg | |
| Filtration System | | |
| Triple filtration system | Filter bag, vac motor filter, & post filter | |
| Vacuum filtration description | Vacuum bag 99.9 @ 0.3 microns | |
| Vacuum hose length | 1.5 ft/ 0.46 m (4:1 stretch ratio) | |
| Vacuum bag capacity | Top fill design; 5L | |
| Power Cord | | |
| Power cord length | 40 ft/ 12 m | |
| Warranty | 1 YEAR ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION. | |