



Feature	Specifications
Product Name/ Model Number:	WB-20 # 9002791
Brush/ Pad Drive System	
Brush Motor rpm:	220 rpm
Brush Motor Watts:	550 watts
Brush Motor HP:	.75 hp
Brush Motor Amps:	20 amps
Brush Motor Voltage:	24 V
Brush/ Pad Design Description:	Single, 20 in/ 50.8 m pad driver
Brush/ Pad Pressure Maximum:	50 lbs/ 22.68 kg
Chassis/ Body Construction	Corrosion-proof rotationally-molded polyethylene
Dimensions	
Product Height:	38 in/ 96.52 cm
Product Length:	47 in/ 119.38 cm
Product Weight:	280 lb/ 127.01 kg (w/ batteries)
Product Width:	22 in/ 55.88 cm
Productivity	
Maximum Coverage Rate per Hour:	20,536 ft ² (1907.79 m ²)
Cleaning Width:	20 in/ 50.8 cm
Battery System	
Battery Amp Hour Rating:	130 amp hour
Battery Count:	2
Battery Run Time per Charge:	Up to 2.5 hr
Coverage per Battery Charge:	77,111 ft².(7163.61 m².)
Recovery System	
Recovery Tank Wet Capacity:	12 gal/ 45.42 L
Squeegee Description:	Forward/ reverse pickup, free-floating, center mounted, urethane blades, 30.25 in/ 76.8 cm
Solution Delivery System	
Coverage Rate Per Tank of Solution:	5476 ft ² (508.72 m ²)
Nominal Solution Flow Rate:	.5 gal (1.89) per minute
Solution Capacity:	10 gal/ 37.85 L
Vacuum System	00 1: (// 07 1: //)
Airflow at Orifice:	66 cubic ft. (1.87 cubic meters) per minute
Vacuum Motor Amps:	14 amps
Vacuum Motor Diameter:	5.7/ 14.48 cm
Vacuum Motor Hp:	.5 Hp
Vacuum Motor Stages:	2 stage
Vacuum Motor Voltage:	24 V
Vacuum Motor Watts:	350 watts
Waterlift at Sealed Orifice:	44 in/ 111.76 cm
Warranty	5 YEARS ROTATIONALLY-MOLDED POLYETHYLENE BODY 1 YEARS/1 YEARS PARTS AND LABOR PLEASE CONTACT TENNANT COMPANY FOR MORE INFORMATION