Clarke

Encore 28-38 Walk-Behind Scrubbers



Full-Size Automatic Floor Scrubbers for Large Cleaning Capacity

The First Choice of Cleaning Professionals

The large Encore can be found cleaning hospitals, schools and shopping malls as well as in industrial applications. After many years of use, both Encore standard and luxury models still provide the greatest value.

- The versatility to configure the machine with various pad drivers or brushes.
- Various battery pack options.
- The off-aisle wand option sprays down water and recovers the solution.
- Choose the standard model or the deluxe feature rich luxury model.
- Large tank capacities mean fewer trips to dump and fill.
- Ergonomically designed controls fit your operator comfortably.

Rugged Features - Designed to Last

Encore large automatic scrubbers provide the longest run times, greatest capacities and lowest costs per day to operate.

Design features include:

- Heavy duty Polydur™ exteriors to prevent accidental damage common in industrial applications.
- Reinforced floating scrub deck with wall rollers and gimbaled floating brushes.
- Heavy duty transaxle cleans inclines and makes for easy loading and unloading.
- Heavy duty rear casters absorb the shock from grouted or damaged floor surfaces.
- Patented Accu-Track™ breakaway squeegee prevents damage if accidentally hooked by a post or pallet.





Service is a Breeze with Encore Automatic Scrubbers





Ergonomically designed operator panel features electronic infinitely variable solution control and a comfortable fatigue reducing handle design. Circuit breakers, charger plug, and drain hose are conveniently located.




Patented squeegee and footprint design on the Encore provide years of maintenance-free operation resulting in perfectly dried floors even in the tightest of turns.

Large Automatic Walk-Behind Scrubbers







KEY FEATURES

- · Operator comfort
- · Stylish design
- · Extended run times
- · Large capacities
- Impressive warranties
- · Transaxle drive
- · Multi-tasking

SPECIFICATIONS

Model	Encore 28	Encore 33	Encore 38
Power Supply /	Encore \$28	Encore \$33	Encore \$38
Charger	36V (6-6V batteries) 250 and 330	36V (6-6V batteries) 250 and 330	36V (6-6V batteries) 330, 370 AH
		115V 60Hz or 230V 50 Hz	
	Encore L28	Encore L33	Encore S38 / Encore L38
	36V (6-6V batteries) 250, 330, 370 AH,	36V (6-6V batteries) 250, 330, 370 AH	36V (6-6V batteries) 250, 330, 370 AH
		115V 60Hz or 230V 50 Hz	
Brush Down Pressu	ire Encore S28	Encore S33	Encore \$38
	150 lbs. (68 kg)	150 lbs. (68 kg)	150 lbs. (68 kg)
	Encore L28	Encore L33	Encore L38
	Variable 120-220 lbs. (54 - 98 kg)	Variable 120-220 lbs. (54 - 98 kg)	Variable 120-220 lbs. (54 - 98 kg)
Vacuum Motor		3-stage tangential discharge / 1 HP (.75 kW)	
Brush Motor	(2) Permanent Magnet / .75 HP (.56 kW)	(2) Permanent Magnet / 1 HP (.56 kW)	(2) Permanent Magnet / 1 HP (.56 kW)
Traction Motor		Transaxle / .5 HP (.37 kW)	
Cleaning Swath	28 in. (71 cm)	33 in. (84 cm)	38 in. (96.5 cm)
Brush Size /	(2) 14 in. (36 cm)	(2) 17 in. (690 cm)	(2) 19 in.(48 cm)
Speed	w/ .5 in. (13mm) overlap 200 rpm	w/ 1 in. (25 mm) overlap 200 rpm	w/ .5 in. (13mm) overlap 200 rpm
Traverse Speed		Variable forward to 230 ft. (70 m) / min.	
Forward / Reverse		Variable reverse to 180 ft. (55 m) / min.	
Recovery / Solution	n Tank	30 / 30 gal. (114 / 114 l)	
Squeegee Size / Ty	pe 39 in. (99 cm)	43 in. (109 cm)	49 in. (125 cm)
		Accu-trac swing w/break-away feature	
Drive Wheels / Casters (2) pneumatic (4.10 / 3.50-6) with sealant (foam optional)			
Dimensions L x W >	c H 62.5 x 28 x 44 in.	63 x 28 x 44 in.	66 x 28 x 44 in.
	(159 x 71 x 112 cm)	(160 x 71 x 112 cm)	(168 x 71 x 112 cm)
Machine Weight w/	/battery 1018 lbs. (462 kg)	1028 lbs. (466 kg)	1038 lbs. (470 kg)
Shipping Weight	1321 lbs. (599 kg)	1331 lbs. (603 kg)	1341 lbs. (608 kg)

WHAT MAKES IT EASY TO USE?

- Ergonomically designed operator controls
- Highly maneuverable with excellent line-of-sight
- Pneumatic drive wheels with added sealant prevent air pressure loss

WHAT ENHANCES ITS PRODUCTIVITY?

- · Large solution and recovery tanks
- Full swing, adjustable squeegee requires no tools
- Transaxle drive system
- · Low maintenance features

DISTRIBUTED BY:

WHAT ARE THE SAFETY FEATURES?

- Solution and brushes are turned off when machine is in neutral
- Unique bristle skirting controls overspray

Clarke®

2100 Hwy. 265 Springdale, AR 72764

 Customer Service:
 1-800-253-0367

 Fax Orders to:
 1-800-825-2753

 Technical Service:
 1-800-356-7274

©2002 ALTO U.S. Inc., All Rights Reserved. Specifications subject to change without notice. P/N 70327A