



Razor® SV17 and E17

- 17" disc scrub deck
- 7 gallon solution and recovery tank capacities
- 17" disc scrub deck
- ECO System™
- Click-off/Click-on disc scrub heads (SV17)
- Onboard battery charger (SV17)
- Maintenance-free gel batteries (SV17)

Razor® 20 and 20T

- 20" disc scrub deck
- 11.1 gallon solution and recovery tank capacities
- ECO System™ allows over 1 hour of scrub time per tank
- Hospital-Quiet, 65.8 dB A sound level
- Onboard battery charger
- Click-off/click-on disc scrub heads (20T)
- Variable speed traction system (20T)



Razor® Plus 24D/26D/28D/24C/28C

- Available in disc (24, 26, and 28 inch) and cylindrical (24 and 28 inch)
- Tools free, interchangeable scrub decks
- Onboard battery charger
- 21 gallon solution and recovery tanks
- ECO System™ allows for enhanced productivity
- Variable scrub pressure
- Click-off/Click-on scrub brushes (disc only)
- Tools free removable brushes (cylindrical)
- Pre-sweeping on cylindrical scrubbers

Models:	Razor® E17	Razor® SV17	Razor® 20	Razor® 20T
Cleaning Width:	17 in (43 cm)	17 in (43 cm)	20 in (50.8 cm)	20 in (50.8 cm)
Max Cleaning Rate Per Hr:	14,960 ft (1,390 m) @ 2 mph (3.2 kph)	22,400 ft (2,081 m) @ 3 mph (4.8 kph)	24,640 ft² (2,289 m²) @ 2.8 mph (4.5 kph)	24,640 ft² (2,289 m²) @ 2.8 mph (4.5 kph)
Scrub Brush/Pad:	(1) 17 inch (43 cm)	(1) 17 inch (43 cm)	20 in (50.8 cm)	20 in (50.8 cm)
Drive System:	Brush Assist	Brush Assist	Pad/Brush Assist	0.3 hp (200 W) variable forward and reverse
Brush Motor:	0.74 hp (550 Watt)	0.70 hp (520 Watt)	0.69 hp (520 Watt)	0.65 hp (480 Watt)
Power Source:	115 V cord electric	(2) 12 V gel batteries	wet-acid and maintenance free available – 20 and 20T	
Brush Max Pressure:	62 lb (28 kg)	51 lb (23 kg)	57 lb (26 kg) standard 70 lb (32 kg) w/optional kit	Two settings: 50 lb (23 kg) and 70 lb (32 kg)
Vacuum Motor:	0.6 hp (450 Watt)	0.44 hp (330 Watt)	0.44 hp (330 Watt)	0.44 hp (330 Watt)
Sound Level:	67 dB A	67 dB A	65.8 dB A	65.8 dB A
Squeegee:	28.3 inch (72 cm)	28.3 inch (72 cm)	29.9 in (75.9 cm)	29.9 in (75.9 cm)
Solution Tank:	7 gal (26 L) capacity	7 gal (26 L) capacity	11.1 gal (42 L) capacity	11.1 gal (42 L) capacity
Recovery Tank:	7 gal (26 L) capacity	7 gal (26 L) capacity	11.1 gal (42 L) capacity	11.1 gal (42 L) capacity
Dimensions:	L: 39 inch (100 cm) W: 22 inch (55.9 cm) H: 33 inch (83.8 cm)	L: 39 inch (100 cm) W: 22 inch (55.9 cm) H: 33 inch (83.8 cm)	L: 48.3 in (123 cm) W: 21.3 in (54 cm) H: 41.7 in (106 cm)	L: 48.3 in (123 cm) W: 21.3 in (54 cm) H: 41.7 in (106 cm)
Weight:	145 lb (66 kg)	140 lb (63 kg) w/o batteries 266 lb (121 kg) w/ batteries	179 lb (81 kg) w batteries 380 lb (172 kg) w/o batteries	212 lb (96 kg) w batteries 400 lb (181 kg) w/o batteries

Models:	Razor® Plus 24D	Razor® Plus 26D	Razor® Plus 28D	Razor® Plus 24C	Razor® Plus 28C
Brush Type:	Disc	Disc	Disc	Cylindrical	Cylindrical
Scrub Path:	24 in (61 cm)	26 in (66 cm)	28 in (71 cm)	24 in (61 cm)	28 in (71 cm)
Max Productivity @ 3.2 mph:	33,800 ft²/hr (3,660 m²/hr)	36,600 ft²/hr (3,140 m²/hr)	39,400 ft²/hr (3,400 m²/hr)	33,800 ft²/hr (3,660 m²/hr)	39,400 ft²/hr (3,140 m²/hr)
Max Productivity @ 1.5 mph:	15,800 ft²/hr (1,468 m²/hr)	17,200 ft²/hr (1,598 m²/hr)	18,500 ft²/hr (1,719 m²/hr)	15,800 ft²/hr (1,598 m²/hr)	18,500 ft²/hr (1,719 m²/hr)
Scrub Head Size or Pad Holders:	(2) 12 in (30.5 cm) brushes or pad holders	(2) 13 in (33 cm) brushes or pad holders	(2) 14 in (35.5 cm) brushes or pad holders	(2) 23 in (58 cm) brushes	(2) 27 in (61 cm) brushes
Power Source:	(4) 6 V batteries (wet-acid and gel cell available) – ALL MODELS				
Brush Speed:	220 rpm	220 rpm	220 rpm	600 rpm	600 rpm
Brush Pressure:	70 lb-110 lb (32 kg-50 kg) variable by gas shock – DISC MODELS			70 lb (32 kg)	70 lb (32 kg)
Brush Motors:	(2) 0.54 hp	(2) 0.54 hp	(2) 0.54 hp	(2) 0.60 hp	(2) 0.60 hp
Solution Control:	Gravity feed, variable from 0.25 gal/min - 1.0 gal/min with ECO (Efficiency Calibrated Orifice) which allows over one full hour of scrub time on a single tank – ALL MODELS				
Solution Tank:	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)
Recovery Tank:	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)
Vacuum Motor:	0.68 hp 3-stage	0.68 hp 3-stage	0.68 hp 3-stage	0.68 hp 3-stage	0.68 hp 3-stage
Sound Level:	66 dB A at operator's position – ALL MODELS				
Drive System:	0.27 hp variable forward and reverse, max speed = 3.2 mph (5.2 km/hr), 10% gradeability – ALL MODELS				
Dimensions (w/o Squeegee):	L: 59 in (150 cm) W: 26 in (66 cm) H: 42 in (107 cm)	L: 59 in (150 cm) W: 27 in (69 cm) H: 42 in (107 cm)	L: 59 in (150 cm) W: 30 in (76 cm) H: 42 in (107 cm)	L: 59 in (150 cm) W: 26 in (66 cm) H: 42 in (107 cm)	L: 59 in (150 cm) W: 30 in (66 cm) H: 42 in (107 cm)
Squeegee Width:	32 in (81 cm)	32 in (81 cm)	34 in (86 cm)	32 in (81 cm)	34 in (86 cm)
Weight:	Machine Only = 265 lb (120 kg), With Max Battery = 539 lb (245 kg) – ALL MODELS				

KENT
Simple. Clean.

14600 21st Avenue North
Plymouth, Minnesota 55447-3408
www.kenturoclean.com
Phone 800-545-4372
Fax 866-261-4779

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.kenturoclean.com
Phone 905-564-1149 or 800-668-8400
Fax 905-564-1030 or 800-263-5111

