## FLOOR MACHINES



## **DESIGN FEATURES**

**EASY OPERATION:** Simple to use, high mounted handle lock with height adjustment and cord release. Large 5-inch non-marking wheels for easy transport.

**SAFETY:** Dual main switch levers and thumb activated safety interlock for left or right-handed operation. Built in circuit breaker to protect motor.

**DURABLE:** Rugged cast aluminum base and switch housing with non-marking bumper to protect facility and machine. Heavy duty steel triple planetary gearbox for smoother operation and longer life.

**OUSTANDING PERFORMANCE:** High torque, 1.5 HP DC motor, 66 frame induction motor for trouble-free operation. Dual capacitor for high efficiency operation and totally enclosed motor protect against dirt and debris provoding a low maintenance machine.

**EXTRAS:** 1.5 inch, cold rolled steel handle tube, with non-marking PVC grips. Heavy duty construction, non-marking PVC bumper.





20" Spirit ..... 1.009-038.0



Continuing our commitment to you today and in the future.

## FLOOR MACHINE **SPIRIT 20**"

## **SPECIFICATIONS**

Motor	66 frame, AC induction motor, Built-in circuit breaker protection, 1.5 HP
Brush/Pad Speed	175 RPM
Pad Diameter	20"
Pad Driver Diameter (Included)	19" (48 cm) Rigid
Construction	Die Cast Aluminum Motor Base & Handle Housing
Wheels	Two, 5" x 11/4", Non-marking
Power Cord	50' with Strain Relief
Weight	105 Pounds
Transmission	Heavy-duty Steel Triple Planetary Gearbox
Dimensions	24.5" x 21" x 47"
Sound Level	63 dBA
Electrical Rating	120 volt, 60 hertz
Optional	Brushes & Sanding Disks Available
Approvals	UL listed to U.S. and Canadian safety standards

