



# Self Contained Carpet Extractors

## 1280

### Walk Behind Extractor

- 20 inch cleaning path
- Large 10 gal. solution and 14.5 gal. recovery tank
- 100 psi pump
- Patented expansion cavity for compact design
- Cleans 3,500 ft<sup>2</sup>/hr



## 1260

### Pull-back Extractor

- 20 inch cleaning path
- Large 10 gal. solution and 14.5 gal. recovery tank
- 100 psi pump
- Patented expansion cavity for compact design
- Cleans 2,600 ft<sup>2</sup>/hr



## 1240

### Pull-back Extractor

- 16 inch cleaning path
- Large 10 gal. solution and 14.5 gal. recovery tank
- 100 psi pump
- Patented expansion cavity for compact design
- Cleans 2,100 ft<sup>2</sup>/hr



## 1220

### Pull-back Extractor

- 16 inch cleaning path
- 7 gal. solution and recovery tanks
- 100 psi pump
- UL approved
- Cleans 2,000 ft<sup>2</sup>/hr



## 1200

### Pull-back Extractor

- 13 inch cleaning path
- 4 gal. solution and recovery tanks
- 60 psi pump
- Lift off recovery tank
- Self adjusting brush
- Cleans 1,400 ft<sup>2</sup>/hr



## Extractor Specifications

Model Number	1280	1260	1240	1220	1200
<b>Vacuum System</b>					
Cleaning path	20"/508 mm	20"/508 mm	16"/406 mm	16"/406 mm	13"/330 mm
Vacuum motor	1.8 hp/13 amp	1.8 hp/13 amp	1.8 hp/13 amp	1.66 hp/10.3 amp	1.5 hp/9.1 amp
Vacuum motor stages	3-stage	3-stage	3-stage	3-stage	2-stage
Waterlift	137"/3480 mm	137"/3480 mm	137"/3480 mm	117"/2972 mm	91.5"/2324 mm
Airflow	101 cfm/2.86 cmm	101 cfm/2.86 cmm	101 cfm/2.86 cmm	99 cfm/2.8 cmm	103 cfm/2.9 cmm
Recovery tank capacity	14.5 gal./55 L	14.5 gal./55 L	14.5 gal./55 L	7 gal./26.5 L	4 gal./13.24 L
Productivity (Per Hour)	3,500 ft <sup>2</sup> /10,67 m <sup>2</sup>	2,600 ft <sup>2</sup> /792 m <sup>2</sup>	2,100 ft <sup>2</sup> /640 m <sup>2</sup>	2,000 ft <sup>2</sup> /610 m <sup>2</sup>	1,400 ft <sup>2</sup> /427 m <sup>2</sup>

### Solution & Brush System

Solution tank capacity	10 gal./38 L	10 gal./38 L	10 gal./38 L	7 gal./26.5 L	4 gal./13.24 L
Solution flow	1 gal./3.8 L/min	1 gal./3.8 L/min	1 gal./3.8 L/min	1 gal./3.8 L/min	.52 gal./1.97 L/min
Spray jets	5	5	5	4	2
Pump pressure	100 psi/7 bar	100 psi/7 bar	100 psi/7 bar	100 psi/7 bar	65 psi/4.5 bar
Pump motor volts	120 V	120 V	120 V	120 V	120 V
Pump motor amps	1 amp	1 amp	1 amp	1 amp	1 amp
Coverage rate per tank	708 ft <sup>2</sup> /66 m <sup>2</sup>	963 ft <sup>2</sup> /90 m <sup>2</sup>	963 ft <sup>2</sup> /90 m <sup>2</sup>	467 ft <sup>2</sup> /43.4 m <sup>2</sup>	433 ft <sup>2</sup> /132 m <sup>2</sup>
Brush rpm	1200 rpm	1200 rpm	1200 rpm	1200 rpm	1200 rpm
Brush motor voltage	120 V	120 V	120 V	120 V	120 V
Brush motor amps	1 amp	1 amp	1 amp	1 amp	1 amp
Brush motor rpm	1800 rpm	1800 rpm	1800 rpm	1800 rpm	1558 rpm

### Total Power Consumption

Amps	14.2 amps	14.2 amps	12.3 amps	12.7 amps	11 amps
Voltage/Watts	120 V/1710 W	120 V/1710 W	120 V/1380 W	120 V/1524 W	120 V/1320 W

### Body Construction

Chassis	polyethylene	polyethylene	polyethylene	polyethylene	polyethylene
---------	--------------	--------------	--------------	--------------	--------------

### Optional Accessories

Hand tool, upholstery tool, crevice tool, solution hose extension, vacuum hose and floor tools

## ***Creating a cleaner, safer world™***

Tennant Company offers the most complete line of floor and surface maintenance equipment, floor coatings, brushes and cleaning detergents in the world for the industrial, commercial and outdoor cleaning markets. Our sales and service networks provide you with integrated custom cleaning solutions to meet any floor care need.



### **Tennant Company Commercial Products**

12875 Ransom Street • Holland, MI 49424  
Toll-free: (800) 982-7658 • Fax: (800) 678-4240  
www.tennantco.com • Email: tcoinfo@tennantco.com

*Authorized Tennant Distributor*