

# Advance GW 4512 & GW 6016 Wet/Dry Tank Vacuums and Air Scoops



Standard Model



AirScoop Model

#### Standard Accessories Include:

- 8 Piece Wet/Dry Tool Kit
- Dry Filter Assembly

#### Some Ideal Applications Include:

- Schools
- Retail Outlets
- Hotels/Motels
- Restaurants
- Health Care
- Institutions
- Offices
- Contract Cleaners

You won't find a better value in a low-cost wet/dry vacuum, especially one with the standard features that come with the Advance *GW 4512* and *6016* vacs.

The *GW* series vacuums come standard with built-in tank drain hoses that control and direct the flow – not just a drain hole that can leave a mess on the floor. They also have a moveable transport handle that folds down over the top of the machine for compact storage, and also makes it easier to load the vac into a vehicle.

The solid tank is heavy-duty, corrosion-proof polyethylene, with thick walls

far stronger than competitive brands. They're simply built to last. The *4512* tank holds 12 gals. (45 l.), the *6016* holds 16 gals. (60 l.).

These wet/dry vacs can also be ordered with a front-mounted *Air Scoop* squeegee attachment that picks up water in forward or reverse.

Replace the overflow prevention cup with the dry filter, and the *GW* vacs are ready for dry pick up. All models come with a complete tool kit.



**Advance**  
by Nilfisk-Advance

# Advance GW 4512 & GW 6016 Wet/Dry Tank Vacuums & Air Scoops



A removable plastic floating cup shuts-off the vacuum air flow to prevent tank overflow.



Simply remove the float cup and insert the dust filter for dry vacuum recovery.



Convenient soft hose gives controlled tank draining, minimizing spills and messes.



Foot pedal raises/lowers the front-mounted squeegee on *Air Scoop* models.



## Satisfaction guaranteed...

- Our products are value-priced to give you the best combination of price and performance for your investment.
- You can get expert service and maintenance for your products by factory-trained personnel around the world, as well as fast parts delivery.
- Maintain peak performance with genuine **apa** parts.

## Technical Specifications

Model	GW 4512/Air Scoop	GW 6016/Air Scoop
<b>Motor:</b>	1.6 hp, 115v/60 Hz, 2-stage	1.6 hp, 115v/60Hz, 2-stage
<b>Sealed Water Lift:</b>	98" (249 cm)	98" (249 cm)
<b>Sound Level:</b>	75 dB(A)	75 dB(A)
<b>Recoverable Tank Capacity:</b>	12 gals. (45 l.) actual	16 gals. (60 l.) actual
<b>Hose Size:</b>	1.5" x 10' (38mm x 3m)	1.5" x 10' (38mm x 3m)
<b>Power Cable:</b>	50' (15 m)	50' (15 m)
<b>Front Wheels:</b>	3" (7.6 cm) swivel casters	3" (7.6 cm) swivel casters
<b>Rear Wheels:</b>	8" x 1.75" (20 cm x 44mm)	8" x 1.75" (20 cm x 44mm)
<b>Front-mount Squeegee:</b>	24" (61 cm) Air Scoops only	24" (61 cm) Air Scoops only
<b>Construction:</b>	injection-molded motor shroud roto-molded polyethylene tank	injection-molded motor shroud roto-molded polyethylene tank
<b>Dimensions:</b>	Height – 26" (66 cm) Width – 17" (43 cm) Length – 22" (56 cm)	Height – 30" (76 cm) Width – 17" (43 cm) Length – 22" (56 cm)
<b>Net Weight:</b>	46 lbs. (21 kg) 53 lbs. (24 kg) Air Scoop	52 lbs. (23.6 kg) 58 lbs. (26.3 kg) Air Scoop
<b>Shipping Weight:</b>	63 lbs. (28.5 kg) 69 lbs. (31 kg) Air Scoop	68 lbs. (30.8 kg) 74 lbs. (33.5 kg) Air Scoop
<b>Part Numbers:</b>	56 209 801 56 209 806 w/Air Scoop	56 209 802 56 209 807 w/Air Scoop

Specifications are subject to change without notice.



Nilfisk-Advance, Inc.  
14600 21st Avenue North  
Plymouth, MN, 55447-3408  
www.nilfisk-advance.com  
Phone: 800-989-2235  
Fax: 800-989-6566

Nilfisk-Advance Canada Company  
396 Watline Avenue  
Mississauga, Ontario, Canada, L4Z 1X2  
www.nilfisk-advance.com  
Phone: 800-668-8400 or 905-712-3260  
Fax: 800-263-5111 or 905-712-3255

