



Model 1550 Specifications

SELF-PROPELLED CARPET EXTRACTOR

Feature	
Solution & Brush System	
Solution tank capacity	32 gallon/ 121 liter
Solution flow	1.2 gallon/min / 4.5 liter/min
Spray jets	6
Pump pressure	100 psi/ 7 bar
Coverage rate per tank	2,700 ft²/ 250 m²
Brush rpm	1,200 rpm
Brush motor	0.5 hp/ 0.37 kW
Vacuum System	
Cleaning path	24-inch/ 610 mm
Vacuum motor (dual motors)	(2) 0.9 hp/ 17 A
Vacuum motor stages	3-stage
Waterlift	135-inch/ 3429 mm
Airflow	152 cfm/ 4.3 cmm
Recovery tank capacity	18 gallon/ 67 liter
Productivity (per hour)	6,000 ft²/ 557 m²
Total Power Consumption	
Amps	50 A
Voltage	36 V
Batteries/cord	3 (12 V)
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.