

## HYDRO-RETRIEVER™ 2052 G / P / B

### RIDER SCRUBBER - SWEEPER

A value-priced, high-production floor cleaner, the industrial *Hydro-Retriever 2052 Scrubber-Sweeper* saves both time and money. Thanks to the 60 gallon (227 l.) solution tank, the 2052 can go 1.5 to 2 hours between refills. That's up to 140,000 sq. ft. (13,000 m<sup>2</sup>) per tankful, so you can get the job done faster. One pass scrubbing and sweeping is usually all it takes to scrub away grease, oil and heavy soil buildup leaving floors clean, dry and safe.

The *Hydro-Retriever 2052* features heavy-duty construction with a rugged worm-gear brush drive so durable it doesn't need maintenance. It can even be used to scarify floors.

No need to pre-sweep floors either. A cylindrical broom picks up dust, oil dry, pallet chips and other light debris, after the scrubbing process. This wet-sweeping process eliminates dust problems and anything that might streak floors in the process.

A new center-pivoting squeegee assembly (G & P models) features a double ball-joint mounting. This new system not only follows uneven floors better, but tracks through tight turns leaving your floors clean, dry and safe.

The *Hydro-Retriever 2052* is available with gas, propane or battery power, and is competitively priced. These machines are an investment in time and labor savings that pay off in practical performance. Consider some of the features and benefits, and ask your Nilfisk-Advance Representative for a free demo.



(Hydro-Retriever™ 2052P Propane model shown)

#### Standard Features Include:

- Four Midlite Grit™ scrub brushes
- Automatic brush shut-off
- Automatic solution shut-off
- Recovery tank clean-out cap
- Automatic squeegee raise in reverse
- Polypropylene main sweeping broom
- Head lights
- Amber safety strobe light
- Wrap-around bumper
- Front roller protectors
- Parking brake
- Key switch
- Hour meter
- Fuel, ammeter, water temp & oil pressure gauges
- 475 amp hour/36 volt battery
- Automatic charger
- Battery condition meter

To maintain the peak performance of your floor maintenance equipment, buy only genuine **apa** parts and accessories.



The wrap-around bumper is formed of 3/16" steel welded to the frame for even greater strength. Optional "shock" towers guard all four corners. Non-marking rollers, built into sturdy corner posts, prevent damage to the 2052 or the facility.



Disc brushes scrub better, last longer, use solution more effectively, and allow the use of pads, and butcher wire brushes or even scarifier tools.



Broom is spiral design around the core for consistent performance. The skirting channels solution and debris to the sweeping broom. The debris hopper pulls out and empties easily. It loads from the top, so it holds more, and is made of aluminum to prevent rust.



The center-pivot squeegee is double ball-joint mounted (G&P models), for better pick-up on uneven floors. The squeegee will last longer because it automatically raises when the machine is backed up.

# S P E C I F I C A T I O N S

<b>Scrubbing Path:</b>	50 in. (127 cm)
<b>Coverage Rate Per Hour:</b>	84,000 sq. ft (7,804 m <sup>2</sup> )
<b>Transport Speed:</b>	0-8 mph (0-13 km/hr) <i>G &amp; P</i> model, 0-6 mph (0-9.6 km/hr) <i>B</i> model
<b>Turning Radius:</b>	2052 <i>G/P/B</i> — 72" (183 cm)
<b>Solution Tank Size:</b>	2052 <i>G/P/B</i> — 60 gal. (227 l.)
<b>Recovery Tank Size:</b>	2052 <i>G/P</i> — 70 gal. (265 l.), 2052 <i>B</i> — 60 gal. (227 l.)
<b>Scrubbing Principle:</b>	Disc
<b>Scrubbing Brushes:</b>	(4) 13.5 in. (34 cm)
<b>Brush Speed:</b>	200 rpm on <i>G &amp; P</i> models, 180 r.p.m. on <i>B</i> model
<b>Brush Pressure:</b>	2052 <i>G/P</i> — 325 lbs. (147 kg), 2052 <i>B</i> — 285 kg (125 kg)
<b>Propelling Motors:</b>	2052 <i>G/P</i> — Hydrostatic, 2052 <i>B</i> — 4 hp electric
<b>Brush Drive Motors:</b>	2052 <i>G/P</i> — Hydraulic, 2052 <i>B</i> — 2.25 hp electric
<b>Vacuum Motors:</b>	2052 <i>G/P</i> — 10 in. (25 cm) belt-driven impeller, 2052 <i>B</i> — 1 hp elec.
<b>Length:</b>	2052 <i>G/P/B</i> — 89 in. (226 cm)
<b>Width:</b>	2052 <i>G/P/B</i> — 54 in. (137 cm)
<b>Height:</b>	With Overhead Guard — 79 in. (210 cm) Without overhead guard — 57 in. (145 cm)
<b>Shipping Weight:</b>	2052 <i>G/P</i> — 3125 lbs. (1417 kg) 2052 <i>B</i> — 2300 lbs. (1043 kg)

All specifications subject to change without notice.

## Product Part Number:

<i>Hydro-Retriever 2052G (Ford)</i>	—	459 500
<i>Hydro-Retriever 2052G w/Hydro-Max</i>	—	459 502
<i>Hydro-Retriever 2052P (Ford) w/LP tank</i>	—	459 501
<i>Hydro-Retriever 2052P w/Hydro-Max</i>	—	459 503
<i>Hydro-Retriever 2052B</i>	—	459 504
<i>Hydro-Retriever 2052B w/Hydro-Max</i>	—	459 505



Nilfisk-Advance, Inc.  
14600 21st Avenue North  
Plymouth, MN, 55447-3408  
www.nilfisk-advance.com  
Phone: 800-989-2235  
Fax: 800-989-6566

Nilfisk-Advance Canada Company  
396 Watline Avenue  
Mississauga, Ontario, Canada, L4Z 1X2  
www.nilfisk-advance.com  
Phone: 800-668-8400 or 905-712-3260  
Fax: 800-263-5111 or 905-712-3255

©1998, Nilfisk-Advance, Inc., Form L1063A, 10/98 Printed in U.S.A.