

Clarke® CA60 scrubber series


Effective cleaning performance

- the next generation of Clarke® Autoscrubbers®



BOOST®

Clarke®
by Nilfisk



Durability: Built Clarke tough

Lower Cost of Ownership: VacSaver float cage, Chemical Mixing System (optional), debris catch cage, onboard charger and isolator warranty

BOOST® Deck Leveling System: Ensures uniform pad pressure front to back for even cleaning

Simplicity: Easy to use, easy to train, easy to maintain

Warranty: Isolators covered under warranty



Control panel with intuitive display for ease of operation



Fully accessible recovery tank with debris catch cage allows for simple cleanup



☒ * Orbital technology cleans with multi directional scrubbing action while using less water and fewer chemicals

BOOST®

Technical specifications

Description	CA60 20D	CA60 20D	CA60 20DT	CA60 20DT	CA60 20B	CA60 20B	CA60 24B	CA60 24B
Solution/recovery tank	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)
Cleaning path	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	24 in.	24 in.
Brush/pad pressure	60 lbs. (27 kg)	60 lbs. (27 kg)	51 lbs. (23 kg)	51 lbs. (23 kg)	88/110 lbs. (40/50 kg)	88/110 bs. (40/50 kg)	88/110 lbs. (40/50 kg)	88/110 lbs. (40/50 kg)
Squeegee width	30 in. (76cm)	30 IN. (76cm)	30 IN. (76cm)	30 IN. (76cm)	30 IN. (76cm)	30 IN. (76cm)	30 IN. (76cm))	30 IN. (76cm)
Sound pressure level	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)
Brush speed	150 RPM	150 RPM	150 RPM	150 RPM	2,250 RPM	2,250 RPM	2,250 RPM	2,250 RPM
Brush motor	0.6 HP, 450W	0.6 HP, 450W	0.6 HP, 450W	0.6 HP, 450W	1HP, 750W	1HP, 750W	1HP, 750W	1HP, 750W
Vacuum motor power	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W
Waterlift	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)
Drive motor	N/A	N/A	.20HP, 150W	.20HP, 150W	.34HP, 250W	.34HP, 250W	.34HP, 250W	.34HP, 250W
Drive type	pad assist	pad assist	traction	traction	traction	traction	traction	traction
Climbing Capacity	2%	2%	2%	2%	2%	2%	2%	2%
Weight no batteries and water	201 lbs. (91 kg)	201 lbs. (91 kg)	214 lbs. (97 kg)	214 lbs. (97 kg)	269 lbs. (122 kg)	269 lbs. (122 kg)	273 lbs. (124 kg)	273 lbs. (124 kg)
Length x Width x Height	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x26x42.5 in. (126x65x108cm)	50x21x42.5 in. (124x53x108cm)
Reference	56385411	56385412	56385413	56385415	56385416	56385417	56385418	56385419

Nilfisk, Inc.
 9435 Winnetka Avenue North
 Brooklyn Park, MN 55445
 Phone: 800.253.0367
 Fax: 800.825.2753
 www.clarkeus.com

Nilfisk Canada Co.
 240 Superior Boulevard
 Mississauga, Ontario, Canada L5T 2L2
 Phone: 800.668.8400
 Fax: 800.263.5111
 www.nilfisk-advance.ca

