M20





Integrated Scrubber-Sweeper

- Superior cleaning results in just one pass—wet or dry—with FloorSmart®
- Maximum productivity with ec-H2O[™] or FaST® for cleaning up to three times longer than conventional scrubbing
- Low total cost of ownership from fully-integrated, cost-efficient design









Superior cleaning results at a low total cost of ownership.



The first fully-integrated scrubber-sweeper, the M20 is engineered for consistent, industrial-strength cleaning whether scrubbing, sweeping or doing both at once.

Dramatically lower total cost of ownership

Without compromising safety or performance, we've reduced the total lifecycle cost of ownership for machines that both scrub and sweep. With two brushes instead of four, EasyOpen™ service access, and 14% fewer parts, the M20 is one of the most cost-efficient industrial cleaning machines available.

Durable, reliable, long-life productivity

The M20 is not two separate machines bolted together like traditional sweeper-scrubbers. Its integrated design, combined with rugged steel and Duramer™ construction, make it simple to maintain and built-to-last.

Safer for operators, customers, and employees

The ErgoSpace™ operator compartment, ec-H2O™ or FaST® technologies, Hygenic® tanks and Grip-N-Go™ corner rollers to protect your facility are just a few of the ways the M20 sets a new standard for safety.



Exclusive Technologies

(optional cleaning innovations)



Electrically converted water

Increase safety

- High traction certified by NFSI
- Reduce chemical accidents

Reduce costs

- Eliminate purchase of daily cleaners
- Reduce water consumption and disposal by up to 70%

Soil type

- Replace daily cleaners
- Effective on food-based oils and greases



Foam-activated chemical

Increase safety

- High traction certified by NFSI
- Eliminate measuring and mixing

Reduce costs

- Reduce chemical usage up to 90%
- Reduce water consumption and disposal by up to 70%

Soil type

 Three grades of chemical from lightduty cleaner to heavy-duty degreaser



Recycled for extended scrubbing

Increase safety

 Reduce chemical handling by 66% (Three cycles maximum per fill)

Reduce costs

 Reduce water consumption and disposal by up to 66%

Soil type

 All grades of chemical – mainly medium cleaner to heavy-duty degreaser

All technologies increase scrub time up to three times

COST-EFFICIENT. PRODUCTIVE. SAFE.

EasyOpen[™] service access reduces downtime, service time and maintenance costs, delivering a dramatically lower total cost of ownership.



Cleaning productivity is increased with a large 3.9 ft 3 / 110 liter, 390 lb / 177 kg debris hopper with 60 in / 1,520 mm variable dump height.



The ErgoSpace™ operator compartment offers outstanding visibility, safety and ergonomics to protect operators, the machine and your facility.

INSIDE THE M20



Ergonomicallyfriendly for operators, the ErgoSpace™ makes cleaning with the M20

safe, easy, and

comfortable.

Reduce training time and simplify operation with the Touch-N-Go™ control panel featuring 1-STEP™ scrubbing and sweeping.

Achieve and reduce component wear with

superior results FloorSmart® an integrated scrubbing and sweeping system.

Superior dust control, excellent shakeback, and high durability from the synthetic panel filter with InstantAccess™ Е

Long-life construction from heavygauge steel frame with T-beam members and Grip-N-Go™ corner rollers. F

Reduce environmental impact with ec-H2O™ or **FaST®** technologies.

KEY AVAILABLE FEATURES

Increase productivity up to 3 hours

Ideal for more porous concrete, ES filters and recycles recovered solution, dramatically extending cleaning time.



Widen the cleaning path from 40 up to 56 inches / 1,020 to 1,420 mm

Achieve superior edge-cleaning capabilities and maximum productivity with an optional side brush.



Boost your cleaning flexibility Spot clean hard-to-reach areas with the 15 ft / 5 m spray hose.



Protect the operator and machine

Ensure safety in severe environments with an overhead guard.

THE NEW M20 VS. COMPETITIVE SWEEPER-SCRUBBERS

New M20 Scrubber-Sweeper

@T2c3

Increased Safety

Costs

Reduced

Maximum Productivity

NFSI-certified to increase traction

ErgoSpace™ operator compartment

Improves visibility

Thermo-Sentry™ hopper sensor

Preventative fire safety

Grip-N-Go™ corner rollers

Facility and machine protection

Triple-sealed electrical connector

UL-certified system protection

Competitive Sweeper-Scrubbers

Water reduction system

Limited operator visibility

No preventative measures

Basic frame protection

Push-on electrical connectors



ес-Н2О™

No chemicals, 70% less water

Two main brushes

Fewer parts to maintain

FloorSmart® integrated machine

Less complexity

On-board diagnostics

Quick, easy maintenance

SmartRelease™ squeegee Reduced replacement parts Conventional detergents

Four main brushes

Two separate machines bolted together

Trial and error

Bolt-on squeegee



ES® with detergent metering The original extended scrubbing system

Smooth front-wheel steering Tight, easy maneuverability

EasyOpenTM service access Quick maintenance, maximum uptime

Wet/dry synthetic fiber panel filter

Increased productivity

Touch-N-GoTM operation Reduced training time, increased productivity

Hygenic® tanks

Minimum downtime with easy access and sanitization

Variable Drain Valves™

No mess

Just detergent metering

Awkward rear-wheel steering

Restricted access, limited serviceability

Paper dust filter, dry-sweep only

Inefficient, multiple-step cleaning

Difficult tank cleanout

Minimal control, messy draining







Tennant Company Environmental Stewardship



ec-H2O[™] and FaST® technologies are NFSI (National Floor Safety Institute) Certified. NFSI certification ensures a product has passed a 2-phase testing process, proving the floor product helps to reduce potential for slip-and-fall accidents.



ec-H2O™ and FaST® technologies are registered by NSF International. NSF International is an independent, not-for-profit organization that ensures formulation and labels on these products meet appropriate food safety regulations.



ec-H2O™ and FaST® technologies may contribute to LEED or **LEED-EBOM (Existing Building: Operations & Maintenance)** points, provided other appropriate criteria are met. For more information on obtaining LEED points, please contact your sales rep or refer to the USGBC website at: www.usgbc.org.



FaST® is a Green Seal (GS-37) Certified Detergent. Green Seal evaluates and certifies cleaning products based on criteria such as the toxicity of the product, skin and eye irritation, skin sensitization, combustibility, toxicity to aquatic life, and packaging.











Resources

Detergents Safety

Improve Reduce Air Quality Noise

Choose GE Capital Solutions and U.S. Bank, our esteemed financial partners, for simple, quick financing with flexible upgrade options, and no long-term obligations.

M20 RIDER SCRUBBER-SWEEPER

Integrated Cleaning System		
Cleaning path	40 in	1,020 mm
With scrubbing side brush	54 in	1,370 mm
With sweeping side brush	56 in	1,420 mm
Cylindrical main brushes		
Brush speed	480 rpm	480 rpm
Brush down pressure (up to)	390 lb	177 kg
Brush diameter (2)	12 in	300 mm
Side brush		
Brush speed	150 rpm	150 rpm
Scrubbing brush diameter	16 in	410 mm
Sweeping brush diameter	21 in	530 mm
Tanks		
Solution tank	56 gal	212 L
Solution capacity with ES®	74 gal	280 L
Recovery tank	73 gal	276 L
Demisting chamber	16 gal	61 L
Debris hopper		
Volume capacity	3.9 ft ³	110 L
Weight capacity	390 lb	177 kg
Dump height (variable to)	60 in	1,520 mm
Vacuum fans		
Scrubbing fan speed	11,000 rpm	11,000 rpm
Scrubbing fan water lift	35 in	890 mm
Sweeping fan speed	6,500 rpm	6,500 rpm
Sweeping fan airflow	290 cfm	8.2 m³/min
Dust Control System		
Filter system	Synthetic fiber panel	Synthetic fiber panel
Filter area	78 ft²	7.3 m ²
Dust filtration (to)	3 microns	3 microns

Dust Control System	Synthetic fiber panel 78 ft² 3 microns Timed, beater bar	Synthetic fiber panel 7.3 m² 3 microns Timed, beater bar			
Filter system Filter area Dust filtration (to) Shaker mechanism (automatic)					
			Propelling System		
			Propel speed forward (variable to)	8.0 mph	13 km/h
			Propel speed reverse (variable to)	3.0 mph	4.8 km/h
Engine-gasoline/LPG (1.6 L)	55 hp	41 kW			

Transport at gross weight Working (cleaning) Ground clearance (transport)	10.0 deg/18% 8.0 deg/14% 3 in	10.0 deg/18% 8.0 deg/14% 80 mm
Machine Dimensions		
Length	95 in	2,410 mm
Width		
Frame	50 in	1,270 mm
Rear squeegee	51 in	1,300 mm
With side brush	58 in	1,470 mm
Height	58 in	1,470 mm
With overhead guard	83.5 in	2,120 mm
Weight (empty)	3,300 lb	1,497 kg

Warranty

Minimum aisle turn

Gradeability

All parts (excluding batteries) have a 36 month warranty under normal use and service, on-site service labor coverage of warranty items for 24 months, and 6 months travel.

110 in

SEEING IS BELIEVING

See for yourself how the M20 scrubber-sweeper delivers clean, safe floors in your most challenging environments. For a demonstration or additional information, call 800.553.8033.

©2011 Tennant and Nobles are registered trademarks of Tennant Company, whose products are

sold and serviced through Tennant Sales and Service Company, as well as through distributors.

Tennant

701 North Lilac Drive Minneapolis, MN 55422 USA

2.790 mm

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315

www.tennantco.com info@tennantco.com