
SC2000™





FACT SHEET



More Productivity in a Compact Scrubber

Combining the productivity and efficiency of a rider with the greater maneuverability of a walk-behind, the SC2000™ micro rider is the most productive 20 inch scrubber on the market today. With a combination of SmartFlow™ technology and 18.5 gallon tanks, operators will extend their time between dump and refill activities by 50% over other 20 inch scrubbers. This additional time results in more time spent cleaning during operators work hours.

SmartFlow™ Technology is just that, Smart

Conventional automatic scrubbers tend to apply more water and cleaning solution on the floor than what is needed, especially when maneuvering around obstacles, slowing down on turns or cleaning along edges. SmartFlow™ technology eliminates extra solution dispensing by automatically reducing the solution flow rate when the machine is slowed down, extending the productivity per tankful. With larger tanks and less solution dispensed, operators will extend the time between dump and refill cycles by as much as 50%. The use of less solution with SmartFlow helps eliminate waste and more importantly, lessens the risk of slip and fall incidents within the facility.

PERFORMANCE KEY FEATURES INCLUDE

- SmartFlow™ technology with detergent/water automatically controlled by speed
- EcoFlex™, debris catch cage and onboard charger standard
- Excellent maneuverability
- Faster than a walk-behind
- 20 inch (51 cm) path with 18.5 gallon (70 L) tanks
- Super quiet for day time operation plus quite mode at 62 dB A
- Multifunction display with One-Touch™ control panel
- Two scrub pressures up to 66 lb (33 kg)

TYPICAL APPLICATIONS INCLUDE

- Offices
- Supermarkets
- Sports Centers
- Shops
- Restaurants
- Hotels
- Hospitals
- Schools





Advance SC2000™

Micro Rider Scrubber



Extremely user friendly and easy to learn. Dashboard with One-Touch button and intuitive display integrated into the steering wheel.



Easy to clean with recovery tank lid completely removable. (Shown with optional safety beacon light.)



Built-in squeegee hanging system on tank allows for safe transportation through doorways and tight areas, while permitting tank drying.



EcoFlex™ System allows for flexible detergent settings with a chemical free cleaning mode and burst of power for powerful spot cleaning at the touch of a button.



Tools-free removable brushes or pads.



Recovery tank fully tiltable gives easy access to battery compartment and EcoFlex™ System.

- 1 Electric actuators for lowering/ raising the deck and the squeegee by pushing a button
- Easy access to operator's seat from both sides; ergonomic working position and foot pedal comfortably placed
- Robust and chemical resistant polyethylene tanks
- 4 Changing cleaning tools is easy with click on/off brushes
- 5 Charging is quick and convenient with onboard charger
- 6 Automatic squeegee lifting in reverse



Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factorytrained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Parts.

Technical Specifications

| Model | SC2000™ X20D |
|--------------------------------------|---|
| Path Width | 20 in (51 cm) disc |
| Tank Capacities | 18.5 gal (70 L) |
| Voltage | 24 V |
| Brush Motor Speed | 155 RPMs |
| Brush Motor | 0.6 hp (450 W) |
| Brush Pressure | 33/66 lb (15/30 kg) |
| Drive Motor | 0.6 hp (400 W) |
| Working Speed | 3.7 mph (6 kph) |
| Max Climbing Rate | 2% |
| Productivity at 3.7 mph | 32,560 ft²/hr (3,025 k²/hr) |
| Productivity at 2.5 mph | 22,000 ft²/hr (2,044 k²/hr) |
| Vacuum Motor | 0.42 hp (310 W) |
| Vacuum Waterlift | 39 in (9.8 KPA) |
| IP Protection Class | X4 |
| Length x Width w/o Squeegee x Height | 50 x 22 x 40 in (127 x 55 x 102 cm) |
| Max Transportation Speed | 3.7 mph (6 kph) |
| Max Running Time | 2.5 hours |
| Minimum Turnaround Aisle Width | 70.9 in (180 cm) |
| Sound Pressure Level | |
| Normal Mode | 68 dB A ±3 |
| Silent Mode | 62 dB A ±3 |
| Squeegee Width | 28.3 in (72 cm) |
| Water Flow (CL/M) | 0,75 / 1,5 / 3,0 |
| Gross Weight | 754 lb (342 kg) |
| Part Numbers | 56384071 – with (2) 130 Ah wet batteries 56384072 – with (2) 140 Ah maint-free AGM batteries |

Specifications are subject to change without notice.



9435 Winnetka Avenue North Brooklyn Park, MN 55445 www.advance-us.com

Phone: 800-850-5559 Fax: 800-989-6566 240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca

Phone: 905-564-1149 or 800-668-8400 Fax: 905-564-1030 or 800-263-5111





