# Adfinity<sup>™</sup> 20D/X20D/X20C/X24D

Advans

# Automatic Scrubbers





Smart cleaning.

A Nilfisk-Advance Brand

# Adfinity<sup>™</sup> 20D/X20D/X20C/X24D

# Automatic Scrubbers



#### Ideal applications include:

- Hospitals / Healthcare Facilities
- Schools and Universities
- Churches and Religious Facilities
- Hotels
- Commercial Cleaning
- Manufacturing Facilities
- Distribution / Warehouse
- Government Buildings and Installations
- Airports, Train Stations, Bus Depots
- Casinos
- Office Buildings
- Health Clubs

## Traction Drive For Increased Productivity.

The new line of Adfinity<sup>™</sup> traction-drive scrubbers from Advance offers multiple versions to choose from for the scrubber size and performance you need. With scrub paths ranging from 20 to 24 inches wide, most of these high-feature models are available with an onboard detergent dispensing system, for the highest level of cleaning productivity.

If you're looking for a scrubber that offers the most efficient use of cleaning chemicals, an Adfinity model with AXP<sup>™</sup> is your answer. Advance's patented AXP Onboard Detergent Dispensing System eliminates guesswork by dispensing detergent at the manufacturer's recommended dilution ratio. Adfinity models with AXP eliminate premixing of chemicals, which saves time and prevents detergent and water waste. Multiple pad pressure settings on select models help to maximize run time, yet still offer more pressure when cleaning highly-soiled areas. All Adfinity machines come standard with an onboard battery charger, allowing the flexibility to charge the machine at any available electrical outlet.

One-Touch<sup>™</sup> operation makes the Adfinity line of scrubbers easy to learn and easy to use. Features not offered on other small disc scrubbers, include Advance's unique "click on" brushes for fast and easy changeovers. Adfinity drive models are equipped with forward and reverse traction drive and an ergonomic and safe paddle design for extra operator comfort. All Adfinity scrubber models are designed for easy access to the battery, detergent dispensing system, where applicable, and the recovery tank.

Adfinity scrubbers are a great addition to any green cleaning program. Operating at a sound level of only 65 dB A, this machine is well below the requirements for sound level set by LEED-EB and GS-42 – making Adfinity ideal for daytime cleaning in any facility. This line of scrubbers also features Smart Solutions<sup>™</sup> flow rate, which is engineered to provide effective cleaning, and the longest run time (over 1.5 hours) on the floor between dump and refills. This saves water and costly chemicals, while increasing productivity. The Adfinity X20D and X24D disc models have received NFSI certification for reducing the possibility of slip-and-fall accidents.



Ergonomic and safe paddle system for operator comfort



Easy to use control panel 1. Scrub 2. Vacuum

- 3. Pad drive click-off
- 4. AXP on/off; set dilution rate at control panel



better traction

Tools-free removable brushes on all model scrub decks



- 1. Solution level indicator also functions as solution drain hose
- 2. Large recovery drain hose with pinch flow regulation
- 3. Rear fill port for solution tank



S

ш

ш Z

ш

മ

AND

ഗ

ш

U R

> . ∢

> ш

ц.

Access to batteries and AXP™ Onboard Detergent Dispensing System



Large recovery tank with easy access to inspect and clean tank. Easy access to ball float shut off.

Simple and intuitive operator controls to minimize training.

Rugged construction with durable components assures years of reliable performance.

Designed to be easy to maintain with open access to all critical systems.

**Safety:** Operating sound level of 65 dB A meets LEED-EB, GS-42 and other green-cleaning noise standards.

#### Environmental Impact: Smart Solutions<sup>™</sup> calibrates solution flow to minimize use of water and detergent.





| Technical Specifications               |   |  |  |  |
|--|---|--|--|--|
| Models                                 | Adfinity <sup>™</sup> 20D   | Adfinity <sup>™</sup> X20D                     | Adfinity <sup>™</sup> X20C                     | Adfinity <sup>™</sup> X24D                     |
| Scrub Head Type                        | Disc  | Disc   | Cylindrical with                               | Disc   |
|  |   |  | debris hopper                                  |  |
| Deck Interchangeability                | All deck types interchangeable – ALL MODELS   |  |  |  |
| Scrub Path                             | 20 in (50.8 cm) pad holder standard;  |  | Dual 20 in (50.8 cm)                           | (2) 12 in (30.5 cm) pad holders                |
|  | brushes available – 20D and X20D  |  | cylindrical brush system                       | standard; brushes available                    |
| Drive System                           | 0.3 hp (200 W) variable forward and reverse<br>Max speed 3.5 mph (5.6 km/hr), 16% gradeability – ALL MODELS |  |  |  |
|  |   |  |  |  |
| Max Productivity @ 3.0 mph (4.8 km/hr) | 26,400 ft <sup>2</sup> (2,453 m <sup>2</sup> )  | 26,400 ft <sup>2</sup> (2,453 m <sup>2</sup> ) | 26,400 ft <sup>2</sup> (2,453 m <sup>2</sup> ) | 31,680 ft <sup>2</sup> (2,943 m <sup>2</sup> ) |
| Scrub Pressure (2 settings)            |   |  |  |  |
| Floating                               | 50 lb (25 kg)   | 50 lb (25 kg)                                  | 57 lb (26 kg)                                  | 61 lb (28 kg)                                  |
| Locked                                 | 70 lb (32 kg)   | 70 lb (32 kg                                   | -  | _  |
| Scrub Head Speed                       | 170 rpm   | 170 rpm  | 570 rpm  | 230 rpm  |
| Solution Flow Rates                    | •   | ·  | ·  | ·  |
| Smart Solutions <sup>™</sup>           | 0.15 gal/min (0.55 L/min)   |  |  |  |
| variable up to                         | 0.3 gal/min (1.1 L/min) – ALL MODELS  |  |  |  |
| Squeegee Width                         | 29.9 in (75.9 cm)   | 29.9 in (75.9 cm)                              | 29.9 in (75.9 cm)                              | 31.9 in (81.0 cm)                              |
| Dimensions (w/o squeegee)              | L = 52.0 in (132 cm)  | L = 52.0 in (132 cm)                           | L = 49.2 in (125 cm)                           | L = 51.6 in (131 cm)                           |
|  | W = 21.3 in (54 cm)   | W = 21.3 in (54 cm)                            | W = 22.4 in (57 cm)                            | W = 25.6 in (65 cm)                            |
|  | H = 42.9 in (109 cm)  | H = 42.9 in (109 cm)                           | H = 42.9 in (109 cm)                           | H = 42.9 in (109 cm)                           |
| Weights                                |   |  |  |  |
| Without batteries                      | 240 lb (109 kg)   | 244 lb (111 kg)                                | 247 lb (112 kg)                                | 243 lb (110 kg)                                |
| With batteries                         | 346 lb (157 kg)   | 350 lb (159 kg)                                | 362 lb (164 kg)                                | 374 lb (170 kg)                                |
| Voltage                                | 24 V – ALL MODELS   |  |  |  |
| Power Source                           | (2) 12 V batteries (wet-acid and maintenance free available) – ALL MODELS                                   |  |  |  |
| Onboard Battery Charger                | 24 V wet/maintenance free compatible – ALL MODELS   |  |  |  |
| Solution Tank                          | 14.5 gal (55 L) – ALL MODELS  |  |  |  |
| Recovery Tank                          | 14.5 gal (55 L) – ALL MODELS  |  |  |  |
| Scrub Motor(s)                         | 0.65 hp (480 W)   | 0.65 hp (480 W)                                | (2) 0.54 hp (400 W)                            | (2) 0.47 hp (350 W)                            |
| Vacuum Motor                           | 0.44 hp (330 W) – ALL   | MODELS   |  |  |
| Sound Level                            | 65.8 dB A at operator's position – ALL MODELS   |  |  |  |
| Approvals                              | ETL, CSA, CE – ALL MODELS   |  |  |  |
| Certification                          | -   | NFSI   | -  | NFSI   |
| Part Number                            | 56317327 w/130 Ah wet-acid bat  | t. 56317329 w/130 Ah wet-acid batt.            | 56317331 w/130 Ah wet-acid batt.               | 56317333 w/130 Ah wet-acid batt.               |
|  | 56317328 w/98 Ah gel batt.  | 56317330 w/98 Ah gel batt.                     | 56317332 w/98 Ah gel batt.                     | 56317334 w/98 Ah gel batt.                     |

Specifications are subject to change without notice.

#### Accessories and options:

- Variety of Scrub Brushes
- Polyurethane Squeegee Blades
- Integrated Solution Fill Hose
- Hour Meter Kit
- Wet Pick-up Wand Kit
- Scrub and Vac Kit
- 20 inch Disc Deck Kit
- 20 inch Cylindrical Deck Kit
- 24 inch Disc Deck Kit

### Smart cleaning.

Our products are designed using innovative technology that increases productivity and drives down the cost to clean.

Maintain peak performance with Nilfisk Genuine OEM Parts.

©2009 Nilfisk-Advance, Inc. Form L1989A 8-27-09

14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com Phone 800-850-5559 Fax 800-989-6566

CE 🌒

240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.com Phone 800-668-8400 Fax 800-263-5111





www.advance-us.com