



Marksman[®] 412

specifications



Vacuum System

Vacuum motor hp	1.5 hp / 0.746 kW
Vacuum motor stages	2 stage
Waterlift at sealed orifice	91.5 in / 2320 mm
Airflow through 2 in orifice	103 cfm

Recovery System

Recovery tank capacity	4 gal / 15 L
Recovery tank description	Lift-off bucket style

Brush Drive System

Brush RPM	1200
Brush motor RPM	1800 rpm
Brush width	10.5 in
Brush bristle type	Nylon construction, four rows of bristles arranged with 360 degrees spiral
Brush diameter	3.375 in / 88 mm

Solution Delivery System

Solution capacity	4 gal / 15 L
Solution pump pressure	60 psi / 4.5 Bar
Solution flow	0.5 gpm / 2 L / min
Solenoid valve	Electronic solenoid valve

Total Power Consumption

Rated amps	12 A
Watts	1400 watts

Power Cord

Power cord length	25 ft / 7.62 m
Power cord type	18 gauge

Dimensions / Weight / Sound Level

Length	22 in / 560 mm
Width	12 in / 330 mm
Height	28 in / 710 mm
Net weight	55 lb / 25 kg

Warranty

3 years/2500 hrs on parts and labor (excluding batteries).
10 years on rotationally-molded polyethylene tanks.