

# WV 900/902

## Wet/Dry Vacuums

The structural foam head of both the 900 and the 1800 series is rustproof and durable. Both the head and the tanks come complete with a 10-year warranty. The flexible dump tube permits quick and convenient emptying to a floor drain while the unique tip and pour system on the 900 series allows the tank to be emptied even when a floor drain isn't available.

A vapor barrier can be added to the units to eliminate moisture simply by putting a 13" floor pad into the top of the wet float assembly to prevent any foam or stripper from reaching the vacuum motor.

For wide-area cleaning, a 29" front-mounted squeegee kit can be fitted to either unit. Units with a front-mounted squeegee can recover water at 10,000 sq. ft. per hour.



WV 900



The unique tip and pour system allows the tank to be emptied even in the absence of a floor drain.



WVD 902



A vapor barrier can be added to eliminate moisture completely

Shown with optional front mount squeegee

MODEL	WV 900 / WVD 902		
Motor	1,200W, 1.6 Hp / 2-800W, 1 Hp	Power Cord	42'
Water Lift	100" / 90"	Weight	44 lbs. / 49 lbs.
Airflow	95 cfm / 160 cfm	Noise Level	64 dB(A) / 67 dB(A)
Capacity	12 gal.	Tank Construction	Structural Foam



QUIET Technology



TIME Saver



SOIL Removal