

S-24XM & S-24

24" / 610 mm SCRUBBERS

PREMIUM SPECIFICATIONS. INDUSTRY FIRST TECHNOLOGIES. AFFORDABLE PRICE.

These 24-inch / 610 mm scrubbers are Purpose Built™ to match your cleaning needs. The S-24XM (extreme maneuverability) is smaller, budget-friendly and great for tight spaces and aisles while still maximizing your cleaning path. The S-24 is larger and can minimize your scrubbing time while fitting into narrow spaces when needed.

A 1,2,3-step training graphics on the control panel!

B Clean on your schedule with sound levels down to 63 dBa

C Don't kneel or strain your back with automatic brush on/off system

D HEPA filtration protects indoor air quality (S-24 only)

E TTS – Tank Treatment System keeps tanks smelling fresh (S-24 only)

F Industry-highest rpm greatly enhances cleaning



AUTOMATED BATTERY PROTECTION SYSTEM

Available on all S-Series scrubbers



APPLICATIONS:

The S-24 disk scrubber is a highly flexible tool for your cleaning regimen. The large, robust tanks and batteries combined with a compact scrub deck is Purpose Built™ for:

- Daily scrubbing of medium sized facilities
- Spill clean-up & water recovery
- Narrow-to-medium width hallways
- Use on uneven floors (dual-disk head)
- Small-to-medium rooms and areas
- Grout and porous floor scrubbing



PACIFIC
FLOORCARE

pacificfloorcare.com

FEATURES

SPECIFICATIONS

MODEL:	S-24XM Disk	S-24 Disk
SOLUTION DELIVERY SYSTEM		
Solution capacity:	11 gal / 42 l	22 gal / 83 l
Solution control: (standard)	0 - .5 gpm / 0-1.9 lpm Variable knob adjustment	0 - .55 gpm / 0-2.1 lpm Variable knob adjustment
Solution control: (with chemical injection)	NA	Low, med & high flow settings (.10, .25 & .45 gpm / .38, .95 & 1.7 lpm) Speed sensitive flow rate or constant output flow rate
SCRUBBING SYSTEM		
Cleaning path:	24 in / 610 mm	24 in / 610 mm
Pad/brush size:	(2) 12 in / 305 mm	(2) 12 in disks / 305 mm
Productivity (per hour) - theoretical max:	26,400 ft ² / 2,453 m ²	26,400 ft ² / 2,453 m ²
Productivity (per hour) - average coverage rate*:	17,325 ft ² / 1,610 m ²	19,525 ft ² / 1,814 m ²
BRUSH DRIVE SYSTEM		
Brush motor horsepower:	1.0 hp / 750 W	1.0 hp / 750 W
Brush rpm:	360 rpm	360 rpm
Brush/pad pressure:	60 & 90 lb / 27 & 41 kg	50, 100 & 140 lb / 23, 45 & 64 kg
Brush/pad attachment/removal:	Automatic on/off	Automatic on/off
RECOVERY SYSTEM		
Recovery tank accessibility:	Full cleanout access	Full cleanout access
Recovery tank capacity:	13 gal / 49 l (2 gal / 7.6 l demisting chamber)	25 gal / 95 l (3 gal / 11.4 l demisting chamber)
Vacuum motor:	.51 hp / 380 W, 2-stage	.7 hp / 522 W, 3-stage
Vac motor cfm / cmm:	68 cfm / 1.9 cmm	71 cfm / 2.0 cmm
Vac motor water-lift:	46 in / 117 cm	71 in / 180 cm
Standard / narrow aisle squeegee width:	30 in/NA / 76 cm/NA	35/30 in / 89/76 cm
DRIVE SYSTEM		
Drive type:	Transaxle drive	Transaxle drive
Motor horsepower:	.25 hp / 187 W	.5 hp / 373 W
BATTERY SYSTEM		
System voltage:	24 V	24 V
Battery amp hour rating:	(2) 12V: 130 AH (wet) / 105 AH (MF)	(4) 6V: 260 AH (wet) / 250 AH (MF)
Battery run time:	Up to 3.5 hours	Up to 5.5 hours
Charger description:	On-board (standard) Off-board (optional)	On-board (standard) Off-board (optional)
MACHINE SPECIFICATIONS		
Product length:	48 in / 122 cm	54 in / 137 cm
Product width (without squeegee):	26 in / 66 cm	26 in / 66 cm
Product height:	43 in / 109 cm	44 in / 112 cm
Product weight (with batteries):	410 lb / 186 kg	650 lb / 295 kg
Sound level (operator's ear):	63 dBA	65 dBA
Construction:	Rotationally-molded polyethylene tanks, powder coated steel frame	Rotationally-molded polyethylene tanks, powder coated steel frame
WARRANTY		
Rotationally-molded tanks:	10 years	10 years
Parts (excluding wear items):	3 years	3 years
Labor:	1 year	1 year

*Productivity calculations utilize key factors from the ISSA 540 cleaning times handbook

Note: Specifications subject to change without notice



GENUINE SERVICE PARTS PURPOSE BUILT™ TO PROVIDE MAX PERFORMANCE

Why buy a copy when you can get the original parts – the ones actually used in the machine's original design work the best. Not only do you get maximum performance, but you also reduce hassle and downtime. Be sure to contact Pacific Floorcare or a local authorized distributor when you need authentic service parts.



PACIFIC[®]
FLOORCARE

pacificfloorcare.com
(800) 968-1332