Razor® Plus



Automatic Scrubbers



Best combination of innovation, quality, and value in walk-behind automatic scrubbers



The Kent Razor® Plus family consists of five models designed on a modular platform to allow tools-free exchange of scrub decks. Three disc models (24D. 26D & 28D) are available featuring "click-off/click-on" scrub heads. The two cylindrical models (24C & 28C) have presweeping capabilities. All models feature 21 gallons solution and recovery capacity, variable scrub pressure, the industry's best sound level, and a standard onboard battery charger. Additionally, the **Economically Calibrated Orifice** (ECO) system allows more than a full hour of productive scrubbing on a single refill/

dump cycle. Options include additional scrub decks for multiple applications, maintenance-free gel batteries, and multiple scrub brushes. The cumulative result is a level of innovation, flexibility, safety, performance, productivity, reliability, and value not previously experienced in walkbehind automatic scrubbers.



Quiet, Clean Operation



Scrub decks are interchangeable with no-tools in less than one minute



Vacuum motor exhausts into heavy-duty tubular steel chassis resulting in ultra-quiet operation



Top cover opens for easy access to recovery tank, vacuum float shut-off, and allows solution tank to be filled from the rear of the machine

21 gallon solution tank combined with ECO system allows over one hour of continuous scrub time without refilling

Heavy-duty, break-away squeegee with tools-free blade rotation and replacement



Cylindrical scrub decks feature tools-free removable brushes.



Counter-rotating brushes deposit loose debris into hopper for sweep/scrub multi-tasking.



Adjustable, ergonomic paddle handle provides comfort and safety.



Simple control panel design give quick access to variable scrub pressure, ECO solution system, and click-off scrub head system (disc models).



Onboard battery charger and charger cord is located on the rear of the machine. Access window provides battery and charger status.

Simple Cleaning Solutions

Tip back tank design allows full accessibility to batteries and all components for simple inspection and maintenance

Machine Only = 265 lb (120 kg), With Max Battery = 539 lb (245 kg), Machine Shipping Weight (batteries shipped separately) = 350 lb (159 kg)

		Razor ^o Plus 26D	Razor [®] Plus 28D		
Brush Type:	Disc	Disc	Disc	Cylindrical	Cylindrical
Scrub Path:	24 in (61 cm)	26 in (66 cm)	28 in (71 cm)	24 in (61 cm)	28 in (71 cm)
Max Productivity @ 3.2 mph:	33,800 ft²/hr (3,140 m²/hr)	33,800 ft²/hr (3,140 m²/hr) 36,600 ft²/hr (3,400 m²/hr) 39,400 ft²/hr (3,660 m²/hr) 33,800 ft²/hr (3,140 m²/hr) 39,400 ft²/hr (3,660 m²/hr)	39,400 ft²/hr (3,660 m²/hr)	33,800 ft²/hr (3,140 m²/hr)	39,400 ft²/hr (3,660 m²/hr)
Max Productivity @ 1.5 mph:	15,800 ft²/hr (1,468 m²/hr)	15,800 (է ^շ /իr (1,468 m²/hr) 17,200 ft²/hr (1,598 m²/hr) 18,500 ft²/hr (1,719 m²/hr) 15,800 ft²/hr (1,598 m²/hr) 18,500 ft²/hr (1,719 m²/hr)	18,500 ft²/hr (1,719 m²/hr)) 15,800 ft²/hr (1,598 m²/hr)	18,500 ft²/hr (1,719 m²/hr)
Run Time:	3 – 4.5 hrs. (variable by b	by battery size and scrubbing application) – ALL MODELS	ipplication) – ALL MODEL	S	
Scrub Head Size:	(2) 12 in (30.5 cm) brushes (2) 13 in (33 cm) brushes or pad holders	(2) 13 in (33 cm) brushes or pad holders	(2) 14 in (35.5 cm) brushes (2) 23 in (58 cm) brushes or pad holders	(2) 23 in (58 cm) brushes	(2) 27 in (61 cm) brushes
Voltage:	24 V	24 V	24 V	24 V	24 V
Power Source:	(4) 6 V batteries (wet acion	(4) 6 V batteries (wet acid and gel cell available) – ALL MODELS	ALL MODELS		
Onboard Battery Charger: 24 V, 25 amp Wet/Gel – ALL MODELS	24 V, 25 amp Wet/Gel – A	ALL MODELS			
Brush Speed:	220 rpm	220 rpm	220 rpm	600 rpm	600 rpm
Brush Pressure:	70 lb-110 lb (32 kg-50 kg	70 lb-110 lb (32 kg-50 kg) variable by gas shock - DISC MODELS	ISC MODELS	70 lb (32 kg)	70 lb (32 kg)
Brush Motors:	(2) 0.54 hp	(2) 0.54 hp	(2) 0.54 hp	(2) 0.60 hp	(2) 0.60 hp
Solution Control:	Gravity feed, variable fro on a single tank	om 0.25gal/min-1.0gal/min v	with ECO (Efficiency Calib	rated Orifice) which allow	e from 0.25gal/min-1.0gal/min with ECO (Efficiency Calibrated Orifice) which allows over one full hour of scrub time
Solution Tank:	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)
Recovery Tank:	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)	21 gal (80 L)
Vacuum Motor:	0.68 hp 3-stage	0.68 hp 3-stage	0.68 hp 3-stage	0.68 hp 3-stage	0.68 hp 3-stage
Sound Level:	66 dB A at operator's po	s position – ALL MODELS			
Drive System:	0.27 hp variable forward	0.27 hp variable forward and reverse, max speed = 3.2 mph (5.2 km/hr), 10% gradeability - ALL MODELS	3.2 mph (5.2 km/hr), 10%	gradeability – ALL MODEI	S
Dimensions	W = 26 in (66 cm)	W = 27 in (69 cm)	W = 30 in (76 cm)	W = 26 in (66 cm)	W = 30 in (66 cm)
(w/o squeegee):	L = 59 in (150 cm) H = 42 in (107 cm)	L = 59 in (150 cm) H = 42 in (107 cm)	L = 59 in (150 cm) H = 42 in (107 cm)	L = 59 in (150 cm) H = 42 in (107 cm)	L = 59 in (150 cm) H = 42 in (107 cm)
Squeegee Width:	32 in (81 cm)	32 in (81 cm)	34 in (86 cm)	32 in (81 cm)	34 in (86 cm)

14600 21st Avenue North Plymouth, MN 55447-3408 www.kenteuroclean.com

Phone: 800-545-4372 866-261-4779 396 Watline Avenue

Mississauga, Ontario, Canada L4Z 1X2 www.kenteuroclean.com

800-668-8400 or 905-712-3260 Phone: Fax: 800-263-5111 or 905-712-3255

SIMPLE. CLEAN.

Kent commercial cleaning equipment is easy to use and made to last.

You can get expert service and maintenance for your products by factory trained personnel around the world, as well as fast parts delivery.

Maintain peak performance with Nilfisk Genuine **OEM Parts.**

Nilfisk Genuine OEM Parts