



Typhoon® EV

specifications



Vacuum System		Typhoon EV 1592	Typhoon EV 1512
Airflow at orifice		103 cfm / 2.9 m³/hr	100 cfm / 2.9 m³/hr
Water lift at sealed orifice		92 in / 2330 mm	120 in / 3048 mm
Vacuum motor hp		1.3 hp	1.6 hp
Vacuum motor amps		8.5 A	10.7 A
Vacuum motor diameter		5.7 in / 140 mm	
Vacuum motor stages		2 Stage	3 Stage
Vacuum motor voltage		120 V	
Vacuum motor watts		980 Watts	1242 Watts
Recovery System			
Recovery tank capacity		15 gal / 56 L	
Vacuum bag capacity		1/3 bushel / L	
Power System			
Power cord length		50 ft / 15 m	
Standard/Optional Accessories			
Standard equipment		10 ft x 1.5 in / 20 mm x 30 mm vacuum hose, standard drain hose. One cloth and one paper filter bag. Contractor tool kit: Dual bend aluminum wand.	
Optional accessories		26 in / 660 mm, 33 in / 830 mm, or 39 in / 990 mm Squeegee attachment kit.	
Dimensions / Weight			
Length		29 in / 730 mm	
Width		15.5 in / 390 mm	
Height		37.5 in / 950 mm	
Net weight		44 lb / 20 kg	
Warranty		3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.	