



Magna Twin™ 3000 specifications



Vacuum System	
Airflow at orifice	208 cfm / 5.89 m ³ /h
Vacuum motor hp	1 hp each
Vacuum motor type	Two 1 hp motors provide 224 cfm at 3 in / 7.62 m ³ / h orifice
Waterlift at sealed orifice	48 in / 1219.2 mm
Brush Drive System	
Brush belt description	Poly-V belt drive
Brush length	26 in / 660.4 mm with edge slots for 30 in / 760 mm path
Brush motor hp	0.25 hp
Brush motor RPM	1200 rpm
Debris Recovery System	
Vacuum bag description	Cloth bag standard; paper bags (99.9 @ .3 microns) optional
Vacuum bag capacity	1 bushel / 1.24 ft ³ / 0.04 m ³
Productivity	
Maximum coverage rate	14,000 ft ² / h / 4,267 m ² / h
Cleaning width	30 in / 762 mm
Power System	
Power cord length	75 ft / 22.86 m
Power cord type	14 gauge, 3-wire; STJ safety yellow
Optional Accessories	
Optional accessories	Hose and Wand Kit (includes all wand mounting hardware, crevice and upholstery tools).
Dimensions / Weight / Sound Level	
Length	39.75 in / 1009 mm
Width	30.5 in / 775 mm
Height	36 in / 914 mm
Net weight	91 lb / 41.28 kg
Sound Level	74 dBA
Warranty	
	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.