



GENERAL SPECIFICATIONS		SWEEPING HEAD		HYDRAULIC SYSTEM	
Total Empty Weight Curb Weight Wheelbase Sweeping Width With One Broom Option Turning Radius Overall Length Overall Width Overall Height	8,000 lbs (3629kg) 5276 lbs (2393kg) 133" (3378mm) 81" (2057mm) 97" (2464mm) 274" (6960mm) 221.1" (5641mm) 89" (2252mm) 77" (1956mm)	Type Operating Direction Suspension Length Blast Hose Diameter Suction Hose Diameter Flap Design	Blast and Suction (right to left) Forward and Reverse 2 Trailing Arms; Spring Balanced 81" (2057mm) 10" (254mm) 10" (254mm) 3 Flaps	Type Fluid Capacity Purpose Cylinders	Piston Pump 33 gal (150l) Power Fan, Gutter Broom, Raise/Lower Hea and Hopper 2 @ 4" x 16" (102mm x 406mr
	77 (173011111)	Control	Hydraulic Raise	OPTIONAL EQUIPMENT	
CHASSIS A selected truck chassis is provided to give		Skids	and Lower Tungsten Carbide	Stainless Steel Hopper Curb Blower	
adequate ratings of all components compatible		ELECTRICAL SYSTEM		Draggin Skids	
with hopper capacity. Consult factory for detailed requirements.		Battery Controls	12 volt 750 CCA Electric; In-Cab Automotive Style	Special Paint LED Bar Light – 24" High Visibility Package	
HOPPER		Circuit Protection		LIMITED WARDANTY	
Volumetric Capacity	2.0 cubic yards		Fuses	LIMITED WARRANTY	
	(1.53 m ³)	WATER SYSTEM		12 month / 1200 hour, 60 month hydraulic system; call for complete details. NOTE: Specifications are subject to change without notice	
Dumping Material Dump Height Dumping Tilt Angle Inspection Doors Controls Paint	Hydraulic Heavy Guage Steel 67" (1702mm) 88 Degrees 1 on Left Side 2 on Right Side Electric; In-Cab	Tank Capacity Construction Pump Controls Filter Mounting Fill Diameter	25 gal (95l) Polythylene Electric 12 Volt Electric; In-Cab Fine Mesh Screen Removable 3" (76.2mm)		
	5000	GUTTER BROOM(S)			
FAN SYSTEM		Туре	Vertical Digger		
Type	Whisper Wheel SM Turbine	Segments Diameter Length	2, Disposable, Poly 16" (406mm) 8.5" (32mm)		
Drive Number of Blades	Hydraulically Driven, Variable 10	Drive Speed	Hydraulic Torque Motor Variable		
Diameter	24" (610mm)	Mounting	Trailing Arm Design		

Location

Suspension

Wear Adjustment

Impact Protection

Tilt Angle Adjustment

Under Cab

Automatic

Spring

Free Floating

Manual; At Broom

Schwarze **S235**

2.0 Cubic Yard Parking Lot Sweeper



800.879.7933 - 1055 Jordan Road, Huntsville AL, 35811

SCHWARZE

INDUSTRIES

INFINITE POSSIBILITIES

AR Hardox Steel

Bolt-In Corded

Overhung Load

For Heavy/Light Material

Rubber

Adapter

National Headquarters:

Construction

Housing Liner

Vacuum Enhancer

Mounting

1055 Jordan Road N. E. • Huntsville, AL 35811

PHONE (256) 851-1200 • FAX (256) 851-1105 • 1-800-879-7933 (toll free US and Canada)

WEB: www.schwarze.com • EMAIL: support@schwarze.com



2.0 Cubic Yard Parking Lot Sweeper





SCHWARZE INDUSTRIES

Since its inception more than 35 years ago, Schwarze Industries, Inc. has grown to become one of the world's largest sweeper manufacturers and a leader in sweeping technology.

> **Conventional Chassis** Gasoline Engine

Automatic Transmission

Low Profile Design

Headquartered in Huntsville, AL., Schwarze has a dedicated workforce of more than 200 employees manufacturing street sweepers, parking lot sweepers and road repair units. In 1996 Schwarze opened a manufacturing facility in Brisbane, Australia to meet the demand for products in other parts of the world.

To date, Schwarze Industries' products operate in more than 35 countries.

Standard Equipment

2.0 cu yd Carbon Steel Hopper 16" Diameter Gutter Broom 24" Diameter AR Hardox Steel Fan Vacuum Enhancer Large Tool Storage Box Backup Alarm Pressurized Dust Control System 81" Reverse Sweep Pickup Head High Visibility Carbide Skids

15.4 Cubic ft of Storage Area **Dual Lockable Steel Latches Durable All Steel Construction** Backpack Storage Area Additional Storage at Rear

Tool Storage Box

24" Whisper Wheelsm Fan

Hardox AR Steel **Rubber Lined Housing** Vacuum Enhancer

2.0 Cubic Yard Hopper

Allows For More Time Sweeping 67" High Dump Welded "No Leak" Steel Construction Large Side Inspection Doors **Exterior Latches**

Aluminum Dump Door

Easy Access For Cleaning Safety Prop **Corrosion Resistant**

Hopper Screen

Easy Access For Cleaning Full Width And Length For

Maximum "No Clog" Airflow

16" Diameter Gutter Broom Vertical Poly Digger In-Cab Controls

Spring Suspension

81" Pickup Head Sweeps In Reverse 10 Inch Diameter Hoses Carbide Skids

Dust Control

25 Gallon Polyethylene Tank 12v High Pressure/ Low Volume

LED Lighting

Built-in Hopper Strobe Lights High Intensity Broom Light

Hydraulic System

Pressure Compensated Piston Pump Variable Speed Fan Adjustment **5 Year Limited Warranty**

Optional Equipment

Stainless Steel Hopper **Curb Blower Draggin Skids Special Paint** LED Bar Light - 24" High Visibility Package

S235 SWEEPER

The Schwarze Model S235 single engine sweeper has been designed to provide a cost effective solution for today's value driven shopping center maintenance client. Powered by a pressure compenstated piston pump driven from the chassis engine, the S235 eliminates the need for an auxiliary engine. Reduced operation costs are quickly realized by lowering fuel consumption requirements as well as costs associated with maintaining an auxiliary engine.

The S235 easily picks up cans, bottles, cups, cigarette butts, paper, diapers, bags and the general litter associated with parking lot maintenance. The low profile (6'5") enables the sweeper to operate in height restricted area such as parking garages. The S235 features a 2 cubic yard hopper capable of dumping into a 67" high receptacle. For those in harsher environments, a Stainless Steel option is available.

At the heart of the S235 sweeper is the pressure compensated piston hydraulic pump which powers the fan, hopper, pickup head and gutter broom hydraulics. The direct drive 24" blower fan allows for variable adjustment for unmatched fuel efficiency and sweeping performance in a wide range of applications. Abrasion Resistant Hardox steel construction and a rubber lined fan housing ensure maximum longevity. An adjustable

vacuum enhancer is also provided for various sweeping conditions. The new "no clog" full width and length hopper screen ensures continuous air flow to maximize performance while minimizing the chance for blockage.

Debris is removed from the surface via an 81" width blast and suction pickup head featuring high visibility carbide skids and the Schwarze "Sweeps in Reverse" design to ensure against damage.

Dust control is provided by a high pressure / low volume pressurized spray system with spray nozzles located at the gutter broom, pickup head and inside the debris hopper. The 25 gallon polyethelene water tank ensures long periods between fill-ups.

The S235 is equipped with a heavy duty lockable steel storage box with ample storage for tools, bags, broom, shovel, and even backpack blower. Built in LED rear strobes and high intensity curb light ensures excellent

Also Available From Schwarze





S335

S350